



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions

---

# CFAST – The Fire Model in the SQA Toolbox for Safety Analysis

2004 DOE/Contractor Fire Protection Workshop  
Las Vegas, NV, June 21-25, 2004

Dr. Allan Coutts, Ph.D.  
Washington Safety Management Solutions  
Aiken, SC 29804, 803.502.9811  
[allan.coutts@wxsms.com](mailto:allan.coutts@wxsms.com)

# Presented at 2004 EFCOG



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions

## CFAST – The Fire Model in the SQA Toolbox for Safety Analysis

EFCOG Safety Analysis Workshop,  
Pleasanton, CA, May 1-6, 2004

Dr. Allan Coutts, Ph.D.

Washington Safety Management Solutions  
Aiken, SC 29804, 803.502.9811  
allan.coutts@wxsms.com

Chip Lagdon, EH-31/GTN

DOE Office of Quality Assurance Programs  
Washington, D.C. 20585, 301.903.4218  
Chip.Lagdon@eh.doe.gov

# Software QA for Safety-Related Software



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- DNFSB TECH-25
  - Issued in January 2000
  - Concluded that SQA for safety analysis software is incomplete
- Recommendation 2002-1
  - Issued September 2002
  - Define Responsibility & Authority
  - Recommend Software
  - Update Directives
  - Conduct Research & Development

# Toolbox Codes to support DSA work



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- Selected Software

- Fire CFAST
- Leak Path Factor MELCOR
- Chemical Release/Dispersion and Consequences ALOHA, EPIcode
- Radiological Dispersion and Consequences MACCS2, GENII.

- Document Access


- [http://tis.eh.doe.gov/sqa/central\\_registry.htm](http://tis.eh.doe.gov/sqa/central_registry.htm)
- Interim guidance reports are issued
- Interim gap analysis reports are issued

# Zone Model Basics



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions



# CFAST Design



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions


- CFAST is a zone model
- Solves Navier-Stokes equations for mass & energy transport
- Separates a fire compartment into two layers
- Each zone is assumed to be uniform (temperature, smoke concentrations, etc.)
- Fire acts as a pump - moves energy and mass between layers - other mixing occurs at doors

# Typical CFAST Results



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions



# Capabilities



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- Accounts for effect of oxygen depletion
- Tracks  $O_2$ ,  $CO_2$ , CO, Soot, HCl, HCN
- Handles 30 fire compartments
- Main and object fires
- Models
  - Natural convection
  - Force convection
  - Changes in horizontal openings



# Principle Limitations



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- CFAST does not evaluate fire behavior, rather it models the response of the building to a fire
- Neglects
  - Radiation feedback from walls that would increase pyrolysis rate
  - Wall flow
  - Radiation transfer through openings

# Available CFAST Versions



**Washington Group International**


Integrated Engineering, Construction, and Management Solutions

- Two actively supported versions
  - Version 3.1.7, published October 2001
  - Version 5.1.1, published May 2004
- Graphical User Interface (GUI)
  - Version 3.1.7 – works for most versions of DOS (95, 98, 2000, ME)
  - Version 5.0 – not ready for prime time

# HRR and Pyrolysis Rate – 3 Trash Bags



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions



# CFAST Libraries & Output



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- Libraries
  - Thermal Properties Database (thermal.df)
  - Object library file (objects.df)
- Output files
  - History file \*.HI
  - Text file (Echo file) \*.txt
  - Spreadsheet file \*.csv
- Other topics
  - CPLOT
  - Graphical User Interface (GUI)

# Graphical User Interface (GUI)



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions


- Permits the automatic generation of the input file
- Is menu driven
- Automatically generates HRR and pyrolysis curves
- Supports modification of thermal library files
- Supports modification of object library files
- Allows pictorial development of mechanical ventilation systems
- Provides estimating tools derived from FIREFORM

# Graphical User Interface – Basic Screen



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions




# DOS – CFAST Command Line



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions

A screenshot of an MS-DOS Prompt window. The title bar reads 'MS-DOS Prompt'. Below the title bar is a toolbar with icons for file operations (Auto, New, Open, Save, Print, Find, Help) and a large 'A' icon. The command prompt shows the following sequence of commands: C:\WINDOWS>cd \, C:\>cd fast, C:\FAST>cd fast317, and C:\FAST\fast317>cfast wtp001.dat wtp001.txt /ri /l\_.

```
MS-DOS Prompt
Auto
C:\WINDOWS>cd \
C:\>cd fast
C:\FAST>cd fast317
C:\FAST\fast317>cfast wtp001.dat wtp001.txt /ri /l_
```

# Possible CFAST Analytical Approach



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- Must address:
  - Analysis uncertainties
  - Facility variability
  - Establish a reasonable degree of analysis margin
- Solution Method
  - Run multiple scenarios
  - Focus on defending design, not obtaining the most accurate representation of a single fire scenario
  - Analysis must consider all potential scenarios



# CFAST Analytical Steps



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

1. Use most likely ventilation conditions & geometry
2. Use a reasonably bounding (nominal) HRR curve
3. Establish the room temperature profile w/CFAST
4. Iterate the ventilation conditions & geometry to maximize temperature
5. Iterate the HRR curve (50% increase in PHRR)
6. Iterate the HRR curve (80% of nominal PHRR)
7. Report the most demanding time-temperature profiles developed above as sufficiently bounding temperature profiles.

# Addressing Flashover Potential



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- Not expected if  $T_{\text{upper}} < 450^{\circ}\text{C}$ .
- Expected if  $T_{\text{upper}} > 600^{\circ}\text{C}$
- Indeterminate if  $450 < T_{\text{upper}} < 600^{\circ}\text{C}$
- If indeterminate:
  - Increase HRR curve slightly (i.e., total energy 2X)
  - $T < 600^{\circ}\text{C}$ , nominal HRR temperature curve is considered representative.
  - $T > 600^{\circ}\text{C}$ : take temperature to be  $600^{\circ}\text{C}$

# Project Plan for CFAST Effort



**Washington Group International**  
Integrated Engineering, Construction, and Management Solutions

- (1) Establish inputs (HRR curves, combustion chemistry estimates, room geometry, etc.) with an appropriate citation
- (2) Conduct CFAST modeling (consider benchmarking to similar problem)
- (3) Produce sensitivity and switchover analysis
- (4) Document analysis

# Conclusion



**Washington Group International**

Integrated Engineering, Construction, and Management Solutions

- CFAST can be used to support DSA preparation
- Users must be knowledge in fire modeling & understand implications of assumptions
- Consider benchmarking results
- Establish consistent analytical approach
- Running the model is only part of the effort